




The Refrigeration Experts

Product specification



XR600H: 600L Cabinet Refrigerator

33-208

Single door refrigerated cabinet

About the product

Affordable. Reliable. Available. XTRA by Foster.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#)

Learn more about our [XTRA Cabinets](#)

Why choose this product

- Supplied with side integrated door handles in lieu of recessed black plastic handles.
- Robust refrigeration at an affordable price
- Microprocessor controller provides simple and accurate temperature control to ensure your food retains its quality and texture
- Hard wearing stainless steel finish to the interior and exterior is stylish and practical
- In stock and available now for immediate shipping
- Full Foster warranty included

Specification

Technical

Temperature	Refrigerator +2/+8°C
Thermal heat rejection (W)	180
Electrical supply	230/50/1
Current (A)	1
Power (W)	180
Refrigerant mass (g)	117
Refrigerant	R290

Dimensions

Height (mm)	1985
Width (mm)	675
Depth (mm)	850
Gross volume (ltr)	600
Net volume	440.27
GN size	2/1
Gross weight (kg)	103
Net weight (kg)	78.5

Build

Cabinet type	Standard
Finish ext/int	304 S/S & 304 S/S
Number of sections	1
Section configuration	Right hinge
System	Integral
Leg type	Braked castors

Energy

Climate Class	5
Energy grade	C
EEI	47.07
AEC (kWh)	627
GWP	3
Energy consumption (kWh/24hr)	1.72

Footnotes

Product specification available in export territories only. Please contact sales@foster-gamko.com for more information.

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.