





Self-contained ice maker - Sprayer system Daily production up to 73 kg

Hotel
Restaurant
Fast food
Bar
Disco
Fish market
Supermarket
Medical & SPA
Industry



► Features

- High melt resistance & clear cube
- AISI 304 SS Scotch Brite finish
- Tropical class +43°C
- Adjustable Stainless Steel feet
- Removable and cleanable air filter
- Air cooled (water cooled option available)
- Easy cleanable internal rounded surfaces
- HCFC-Free insulated storage
- RoHS Free
- Disappearing insulated door
- Electromechanical operation
- ON-OFF rocker switch
- Standard voltages
- HFC Free - R290 Refrigerant
- Automatic Washing system
- Internal drain pump



Green-Tech Design



Side openings for better ventilation




Double water inlet (W models only)



Plug-in electrical connection

► Available ice cube size



Cube 23 grams
dimensions H 31.5 x L 32.5

► Prod. 24h

	Air temp.		Water temp.		kg	lbs
°C	10°C	50°F	7°C	45°F	73	161
	21°C	70°F	15°C	60°F	72	159

2 Years Warranty
subject to limitations

► Certifications available for this model






B72/40A HC DP



Self-contained ice maker - Sprayer system Daily production up to 73 kg



► Working conditions

- Location: **Indoor**

	Min	Max
Ambient temperature	+10° C / +50° F	+43° C / 110° F
Water temperature	+3° C / +37° F	+32° C / +90° F
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

► Performance

		Water temperature					
		7° C	45° F	15° C	60° F	21° C	70° F
		10° C	73 kg				
Air temperature	50° F		161 lbs				
	21° C			72 kg			
	70° F				159 lbs		
	32° C					62 kg	
	90° F						137 lbs

► Connections

All measurements are referenced from the rear bottom-left corner (L-H-Ø)

- ① Water in: 135 mm / 5 5/16" - 122 mm / 4 13/16" - 3/4"
- ② Water out: 62 mm / 2 7/16" - 182 mm / 7 13/16" - 24 mm / 1 5/16"
- ③ Electrical connections: 100 mm / 3 15/16" - 252 mm / 9 15/16"
- ④ Cond. water in: 124 mm / 4 14/16" - 208 mm / 8 3/16" - 3/4"
- ④ Only for water cooling systems

► Technical information

Production in 24h	72 kg / 159 lbs
Store capacity, up to	40 kg / 88 lbs
Cooling system	A
Kind of cube	23g
Refrigerant	R290
Standard voltage	220-240 V ~ 50 Hz
Average power consumption	590 W
Fuse	10 A
Electrical consumption	22 kWh/100kg

All the technical information must be considered at the following conditions:

- Sizes without feet
- Standard Cube (23 g)
- Ambient temperature +21° C
- Water temperature +15° C
- Electrical consumption at +32° C (standard voltage)
- Average power consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice

Water consumption	A: 4 l/kg - 47,9 gal/100 lbs
	W: 16 l/kg - 191,7 gal/100 lbs
Sizes (L-P-H mm)	735 - 603 - 850
(L-P-H in)	28 15/16 - 23 12/16 - 33 7/16
Sizes with pack (L-P-H mm)	780 - 640 - 1015
(L-P-H in)	30 11/16 - 25 3/16 - 39 15/16
Net weight	67 kg / 148 lbs
Gross weight	79 kg / 174 lbs
Finish	AISI 304 stainless steel, scotch brite

Rev. 02 - Issued June 2025



www.maidaid.co.uk

sales@maidaid-halcyon.co.uk

03457 308070