



SLICER GSM-250 220/60/1

Ø 250 mm blade.



5051031



DYNAMIC PREPARATION
COMMERCIAL SLICERS

SALES DESCRIPTION

Belt driven slicer.

- ✓ Slicer made of a special anodized aluminum alloy, hygienic, and anticorrosive.
- ✓ Professional slicer with blade protective ring and carriage lock.
- ✓ High-powered ventilated motor.
- ✓ Easy-to-mount sharpener.
- ✓ Decimal thickness adjustment from 0 to 14 mm.
- ✓ Plate mounted on self-lubricating bushings and bearings.
- ✓ Easy cleaning, no need for tools. Dishwasher-safe detachable grip points.
- ✓ Luminous double on/off 24V switch.
- ✓ Safety print.

INCLUDES

- ✓ Blade removal tool.

SPECIFICATIONS

Blade diameter: 250 mm
Cutting capacity: 190 mm x 220 mm
Slice thickness: 0 mm - 14 mm
Carriage run: 215 mm
Total loading: 220 W
IP Protection grade: X1
Electrical supply: 220 V / 60 Hz / 1~
Plug: EU

External dimensions (W x D x H)

- ✓ Width: 620 mm
 - ✓ Depth: 425 mm
 - ✓ Height: 370 mm
- Net weight: 15.5 kg
Crated dimensions
540 x 470 x 440 mm
Gross weight: 18 kg



SAMMIC, S.L. · Basarte, 1
20720 AZKOITIA (Gipuzkoa) · SPAIN



sammic.co.uk

Food Service Equipment Manufacturer

Unit 2, Trevanah Road

Troon Industrial Park

LE4 9LS - Leicester

uksales@sammic.com

Tel.: +44 0116 246 1900



Project

Date

Item

Qty

Approved

product sheet
updated 19/11/2025