

SPH515S

Family	Professional dishwasher
Subfamily	Hoodtype dishwasher
Serie	Easyline
Basket dimensions	500x500 mm
Power connection	400 V 3N~ / 16 A / 9,7 kW / 50 Hz
Simultaneous heating	Yes
Width	635 mm
Depth	750 mm
Height	1510 mm
Maximum height with open hood	2102 mm
Usable load height	470 mm



Target

Solutions	Coffee shops/Wine bars; Hotels; Restaurants/Pubs; Food retail; Catering and Institutions; QSR
-----------	--

Aesthetics

Control panel	electronic	Led color	White
---------------	------------	-----------	-------

Functions



Functionality	GN 1/1 trays washing; Triple filter; HTR; Door clearance 470mm
---------------	--

Programs

Programs

Boiler 71°C/Tank 60°C - 1'20"	Boiler 85°C/Tank 60°C - 1'10"	Boiler 85°C/Tank 60°C - 2'
Boiler 85°C/Tank 60°C - 3'	Boiler 71°C/Tank 60°C - 2'10"	Boiler 85°C/Tank 60°C - 4'10"
Drain and self cleaning cycle	Yes	
Maximum basket/hour	51	

Maximum dishes/hour 918

Interface

Panel	Easyline	Rinse aid missing alert	Yes
Display	8 digit	Detergent missing alert	Yes
Number of buttons	5	Cycle progress alert	Yes
On/Off button	Yes	End-cycle alert	Yes
Salt alert	Yes	Manual diagnostic	Yes

Construction

Tank	Deep drawn	Tank capacity	14 l
Tank	Double wall	Boiler capacity	8 l
Tank material	Stainless steel AISI 304	Noise	Lpa 59,9 dBA
Back panel	Prepainted	Protection class	IPX4
Tank filter	Stainless steel	Net weight	127.000 kg
Washing spray arm	2 in stainless steel	Adjustable feet	95 mm
Rinse spray arm	2 in stainless steel	Drain max. height	1000 mm

Consumption and connections

Tank heating element	2200 W	Water cycle consumption	3,2 l
Boiler heating element	9000 W	Warm water connection	Cold 15°C
Washing pump	700 W	Max temperature inlet water	60°C
Default connection	9700 W	Max water hardness	54°FH - 30°dH
Optional electrical connection	230 V 3~ / 28 A / 9,7 kW / 50 Hz; 230 V~ / 16 A / 3,7 kW / 50 Hz (NC); 230 V~ / 29 A / 6,7 kW / 50 Hz	Inlet pressure	100-600 kPa

Electrical Connection

Plug	Not present
------	-------------

Manuals and Certifications

Certificate	CE, UKCA
-------------	----------

Equipments

Peristaltic detergent doser	Electronic control	Drain pump with 3 stage filter system	Yes
Detergent (red) hose lenght	2,2m	Rinse pump H.T.R. system	Yes
		Break tank	Yes

Automatic incorporated softener	Yes	Partial renewal of water in the tank and built-in drain pump	Yes
Peristaltic rinse-aid doser	Electronic control	Water supply pipe diameter	DN15 - ½"
Detergent load	1,5 l/h	Drain supply pipe diameter	DN20-G 3/4"
Rinse aid (blue) hose lenght	2,2m	Automatic start	Yes, default OFF
Rinse load	0,4 l/h	Chemicals level probe	Yes, optional KITSONLIV
Boiler thermostop	Yes default ON	Trays washing option	Yes
Deafult chemicals dosing unit of measure	gr/lt	GN1/1 530x325mm	

Accessories Included

Dish basket	1x PB50D01	Water supply hose	Yes - 2m
Cutlery basket	1x PHOOS02	Drain hose	Yes - 2m
Flat basket	1x PB50G02		

Not included accessories



WT5700SR

Entry table right side with sink, backsplash (100mm), lower shelf, 700x720x821,5 mm



WTX51200

Exit table for both sides, with lower shelf, 1200x560x821,5 mm



PHOOS03

8 compartments polypropylene basket for cutlery suggested for Hood Type



WT5700SL

Entry table left side with sink, backsplash (100mm), lower shelf, 700x720x821,5 mm




WT51200SHL

Entry table left side with sink and scraping hole, backsplash (100mm), lower shelf, 1200x720x821,5



PHOOS01

Polypropylene single basket for cutlery



PB50G02

Universal flat bottom polypropylene basket, 500x500x170 mm



WTX51200L

Exit table left side, with backsplash (100mm), with lower shelf, 1200x720x821,5 mm



WB50G01

Universal wire basket with flat bottom, 500x500x123 mm



WH00C01

Wire insert for cups



WT51200SR

Entry table right side with sink, backsplash (100mm), lower shelf, 1200x720x821,5 mm



KITSONLIV

Probe level kit for double wall models

WG4646

Grid for light objects, 460x460 mm



WH00S01

Wire insert for 12 small dishes



WTX5700R

Exit table right side, with back splash (100mm) and lower shelf, 700x720x821,5 mm



WB50T02

Wire basket for 7 trays GN1/1 h 20 mm, 500x500 mm



WT51200SHR

Entry table right side with sink and scraping hole, backsplash (100mm), lower shelf, 1200x720x821,5 mm



WT51200SL

Entry table left side with sink, backsplash (100mm), lower shelf, 1200x720x821,5 mm

**PB50D01**

Polypylene basket for 18 plates,
500x500x105 mm

**WTX51200R**

Exit table right side, with backsplash
(100mm), with lower shelf,
1200x720x821,5 mm

**WTX5700**

Exit table for both sides, with lower
shelf, 700x560x821,5 mm

**WB50D01**

Wire basket for 18 dishes 250 mm max.
diameter or self service trays, 500X500
mm

**WTX5700L**

Exit table left side, with back splash
(100mm) and lower shelf,
700x720x821,5 mm

**WB50G02**

Wire basket for 90 mm diameter max
glasses with sloped bottom,
500x500x170 mm

**WB50G04**

Wire basket for glasses 135 mm
diameter max, with sloped bottom,
500x500x170 mm

**PHOOS02**

6 compartments polypropylene
basket for cutlery

**WB50G03**

Wire basket for 72 mm diameter
glasses with inclined bottom,
500x500x235 mm

Symbols glossary (TT)



SUITABLE FOR GASTRONORM TRAY



HTR RINSING SYSTEM



PARTIAL DRAIN SYSTEM+

